



# Eurofondo

## Solvent Based Bituminous Primer



**Properties.** Eurofondo is a solvent based bituminous primer for priming concrete roofs, walls and floors, cement screeds, bitumen felts, weather corrugated iron and steel prior to the application of bituminous materials. Eurofondo uses as solvent a selection of aliphatic and aromatic hydrocarbons and forms a solution that seals any pores on the surface it is applied and forms a film upon drying.

**Application.** Application is usually done by spraying, brush or mop. A typical application rate is between 0.1 and 0.2 L/m<sup>2</sup>.

### Technical Data

Properties	Eurofondo (MIN/MAX)	Test Method
Application Temperature	0 – 50 °C	
Service Temperature	0 – 120 °C	
Specific gravity	0.92 g/cm <sup>3</sup>	
Flash Point (Tag Open-Cup) °C	37 °C	ASTM D1310
Volatiles by Distillation	48-52%	ASTM D402
Penetration at 25 °C, 100g, 5 sec.	≤ 50	ASTM D5

**Packing.** Eurofondo is available in 20 L and 200 L drums.

**Health and Safety.** Suitable protective equipment needs to be worn at all times. Full skin protection is required. Avoid exposure to fumes by standing back when you open a sealed container, until vapors have dispersed. The product is moderately flammable. See MSDS for further information.

A.N.C Waterproofing Industries, Ltd.  
Anatolikon Industrial Area  
P.O. Box 60268  
Paphos 8101 - Cyprus  
Tel: +357 26422860 Fax: +357 26422684  
e-mail: ancwater@cytanet.com.cy